未注公差/General tolerances(mm)

0 ~ 3	>3 ~ 6	>6 ~ 10	>10 ~ 18	>18 ~ 30	>30 ~ 50	>50 ~ 80	>80 ~ 120	>120 ~ 180	>180 ~ 250	>250 ~ 315	>315 ~ 400	>400 ~ 500	>500	0.05/10
±0.08	±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±1°

污染等级/Pollution degree	II
过压类别/Overvoltage Category	CAT III
额定电压电流/Rated Voltage/Current	2000VDC/40A
接触电阻/Contact resisance	≤0.5mΩ
使用温度范围/Operating temperature(° C)	-40° C - +85° C
防护等级/Levels of protection	IP68(1m,24h)
防护等级(未插合)/Levels of protection	IP2X
连接类型/type of termination	压接/Crimping
线径范围/Wire range	4-6mm2











建议开孔尺寸/Suggested hole size
建议板厚/Suggested plate thickness 2-5mm

DEGSON	MATERIAL: 材质		SURFACE/COLOR: 表面处理
	MAT NO./REV: 29050000015 / 版本		MAT STATUS: 物料状态
APPD: 核准人	核准日期	NAME	
CHKD: 审核人	审核日期	PV-DC-FM-PSC-01P-40A-8-00ZH	
DRFT: 设计人	设计日期	DRAWING NO. 图号	TYPE 图纸类型
A4	mm (inch)	DRAWING STATUS 图纸状态	SCALE 1:1 / SHEET 1/1

图纸版本	ECN	变更描述	设计人	设计日期
REV	ECN	DESCRIPTION	DRFT	DATE

Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 除非经予明确授权，否则禁止转让、复制、利用、交流本文件的内容，侵犯者将负赔偿责任。本公司保留对涉及实用新型或外观专利的所有权利。