Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 除非经予书面授权，否则禁止将此、复制、利用、交流本文件的内容，侵犯者将负赔偿责任。本公司保留对涉及发明、实用新型或外观专利的所有权利。

未注公差/General tolerances(mm)														
0 ~ 3	>3 ~ 6	>6 ~ 10	>10 ~ 18	>18 ~ 30	>30 ~ 50	>50 ~ 80	>80 ~ 120	>120 ~ 180	>180 ~ 250	>250 ~ 315	>315 ~ 400	>400 ~ 500	>500	0.1/10
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	±2°







Wiring diagram



X1

Laser Printing Front Note:
DEGSON®
Laser Printing Back Note(Arial):
MEAC-T-032A-P21-03-5.0M-10AH 32A 480V AC IEC 62196-2:2022 IP67 20xxxxxx-xxxx

X2

Laser Printing Front Note(Arial):
MEAC-T-032A-V21-03-5.0M-10AH 32A 480V AC IEC 62196-2:2022 IP67 20xxxxxx-xxxx
Laser Printing Front Note:
DEGSON®



额定电压电流/Rated Voltage/Current	480V AC/32A
绝缘电阻/Insulate Resistance	>100MΩ,500V DC 1min
耐压/Withstanding Voltage	L、N and PE ,2500V AC 1min L and N ,2500V AC 1min
防护等级/Ingress Protection	IP67
插拔寿命/Insertion/Pullout Times	10,000 Times
插拔力/Insertion/Pullout Force	<100N
使用温度范围/Operating temperature(°C)	-30~+50
线材规格/Cable specification	5*4mm²+1*0.5mm² Black
标准/Reference standard	IEC 62196-2:2022
符合RoHS环保要求/Conform to RoHS	Yes

REV	ECN	DESCRIPTION	DRFT	DATE

DEGSON

APPD:
CHKD:
DRFT: Rong QX 2024.12.17

A4 mm (inch)

MATERIAL: SURFACE/COLOR:
MAT NO./REV: /D0-1 MAT STATUS:
NAME MEAC-T-032A-V21P21-03-5.0M-10A(H)

DRAWING NO.	TYPE	DRAWING STATUS	SCALE	SHEET
	CUSTOMER DRAWING		1:3	1/1